



DATA SHEET

USB-C[®] to HDMI[®], VGA, USB-A, and RJ45 Multiport Adapter – 4K 30Hz

Connect to a USB-C laptop for video, wired network connectivity, and data transfer

OVERVIEW

The USB-C to HDMI, VGA, USB-A, and RJ45 Multiport Adapter connects to USB-C or Thunderbolt™ 3 enabled laptops and is perfect for contributing to a desktop solution—making it ideal for inside reps that need essential connectivity while in the office or when working from home.

This multiport adapter offers a lightweight, portable, and easy way to deliver audio/video and transfer data. Connect to a USB-C equipped laptop or tablet, display HDMI audio/video or VGA video content, plus transfer data and connect to a network.

Supporting resolutions up to 4K at 30Hz for HDMI and 1920x1200 at 60Hz for VGA, this multiport adapter mirrors or extends a high-quality video image to the connected display. The USB-A data port supports SuperSpeed USB 5Gbps data transfers—allowing up to 32GB of data to be downloaded in under a minute. The Ethernet port allows for reliable internet connectivity with file transfer speeds up to 1000Mbps.

Note: When both video ports are connected, HDMI and VGA display the same image with resolutions up to 1080p at 60Hz.

FEATURES

- Supports HDMI Resolutions up to 4K at 30Hz, for viewing your screen content at full HD
- Supports VGA Resolutions up to 1920x1200 at 60Hz
- Supports USB 3.0 SuperSpeed (5Gbps) Transmission for fast data transferring
- Hard wired Ethernet port for when security requires it or when WiFi™ is not available
- Reversible, symmetrical USB-C connector, so no guessing how to plug it into your laptop

ITEM DESCRIPTION

C2G29828	USB-C to HDMI, VGA, USB-A, and RJ45 Multiport Adapter-4K 30Hz – Black
C2G29829	USB-C to HDMI, VGA, USB-A, and RJ45 Multiport Adapter-4K 30Hz – White

SIGNAL SPECIFICATIONS

- Supports HDMI Resolutions up to 4K at 30Hz
- Supports VGA Resolutions up to 1920x1200 at 60Hz
- Supports 10/100/1000Mbps Bandwidth
- Supports USB 3.0 SuperSpeed (5Gbps) Transmission, Downward Compatible with USB 2.0

Note: When both video ports are connected, HDMI and VGA display the same image with resolutions up to 1080p at 60Hz

ELECTRICAL SPECIFICATIONS


- Rating: Temp 80°C; Voltage 30V
- Conductor Resistance: At 20°C Max; 34AWG: 860 [OHM]/KM
- Insulation Resistance: 10M - KM Min at 20°C; DC 500V (EIA-364-21)
- Dielectric Strength: AC 500V/1 Minute No Breakdown (EIA-364-20)

PHYSICAL SPECIFICATIONS

- Operating Temperature: 0°C to +45°C; 10 - 85% RH (Non-Condensing)
- Storage Temperature: -10°C to +70°C; 5 - 90% RH (Non-Condensing)

PHYSICAL CHARACTERISTICS

- Molding Material: PVC; Conforms ROHS
- Connector 1: USB 3.1 Type-C Male: Contacts Terminal Gold Plated 3U, Nickel Plated Shell; Black Insulation
- Connector 2: HDMI Female: 19 Pin A/F Iron Shell Nickel Plated, Terminal Gold Plated G/F with PCB
- Connector 3: VGA Female: Front Rivet Nut, Iron Shell Nickel Plated, Black Core with PCB
- Connector 4: RJ45 Female: Iron Shell Nickel Plated, Black Core, Pin Gold Plated with PCB
- Connector 5: USB-A Female: Blue Adhesive (PA9T) Iron Case Nickel Plated, Pin Gold Plated with PCB
- Product is CE Marked and Conforms to 2011/65/EU ROHS 2 64.2mm / 4.3" x 0.6" x 2.5"



LEGRAND | AV COMMERCIAL BRANDS

C2G | Chief | Da-Lite | Luxul | Middle Atlantic | Vaddio | Wiremold

SIMPLIFIED CONNECTIVITY

USA 800.506.9607 | c2g.com | legrandav.com | customer-service@c2g.com

EMEA +31 495 580 840 | c2g.com/uk | legrandav.com | c2g.emea@av.legrand.com

©2021 Legrand AV Inc. 210463 Rev A 7/20 C2G is a registered trademark of Legrand AV Inc. All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All patents are protected under existing designations. Other patents pending.